

B12Y Series (N Male-ST to N Male-ST)

High Performance Cable Assembly, 50ohms, DC-18GHz



B12Y-07-07-"L" (L: Length)

Maximum Ratings

Operating Temperature -55°C to +85°C
 Storage Temperature -55°C to +85°C
 Permanent damage may occur if any of these limits are exceeded

Cable Diameter	4.9mm	
Velocity of Propagation	83%	
Shielding Effectiveness	>90dB	
Power Handling at 20°C	1 GHz	875W
	2 GHz	615W
	6 GHz	350W
	12GHz	244W
	16 GHz	210W
18 GHz	197W	
Min. Bending Radius	20mm	


Features

- Stainless steel connectors for long mating-cycle life
- High shielding effectiveness, >90dB
- Excellent phase stability over temperature, 500ppm@-55°C~+85°C
- Extremely low loss, low VSWR
- High power handling

Applications

- Phase array radars
- Rack to rack connection
- RF/Microwave test systems
- Airborne, ground and shipborne systems


Outline Drawing Unit [mm]



Electrical Specifications at 25°C

Freq. (GHz)	Length (m)	Insertion Loss (dB@GHz)								VSWR (@GHz)							
		DC - 3		3-6		6-12		12-18		DC - 3		3-6		6-12		12-18	
		Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.
DC-18	0.5	0.4	0.5	0.5	0.6	0.6	0.8	0.7	0.9	1.09	1.15	1.12	1.20	1.18	1.25	1.30	1.35
	1	0.5	0.7	0.7	0.9	1.0	1.2	1.2	1.5								
	1.5	0.7	0.9	0.9	1.1	1.5	1.7	1.8	2.1								

Cable Cross Section



Typical Performance Data (B12Y-07-07-1M)

Frequency(MHz)	VSWR	Insertion Loss (dB)
50	1.02	0.03
1000	1.05	0.25
2000	1.07	0.35
3000	1.09	0.43
4000	1.10	0.50
5000	1.11	0.57
6000	1.12	0.64
7000	1.13	0.72
8000	1.14	0.79
9000	1.15	0.85
10000	1.16	0.90
12000	1.19	0.97
13000	1.20	1.03
15000	1.23	1.15
18000	1.30	1.24

Cable Construction	
Inner Conductor	Solid Silver Plated Copper
Dielectric	LD-PTFE
Inner Braid	Silver-Plated Copper Strip
Outer Braid	Silver-Plated Copper Braid
Jacket	FEP

Connectors	
• Nut, Stainless steel, Passivated	
• Body, Stainless steel, Passivated	
• Center contacts, Brass, Gold plated	
• Dielectric, PTFE, Natural	

Product Guarantee*
 Micable will repair or replace your cable assembly if it fails within six months after shipment. This guarantee excludes product damage from misuse or abuse

