

# E01 Series (SMP Female-ST to SMP Female-RA)

.047 Semi-rigid Cable Assembly, 50ohms, DC-40GHz



## E01-37-38-"L" (L: Length)

### Maximum Ratings

Operating Temperature -55°C to +125°C

Storage Temperature -55°C to +125°C

Permanent damage may occur if any of these limits are exceeded

Cable Diameter	1.19mm	
Velocity of Propagation	70%	
Shielding Effectiveness	>120dB	
Power Handling at 20°C	1 GHz	32W
	6 GHz	14W
	12 GHz	9W
	18 GHz	8W
	26.5 GHz	7W
Min. Bending Radius	4.2mm	


### Features

- Frequency DC-40GHz
- Excellent return loss/VSWR
- High shielding effectiveness > 120 dB
- 3-D bending without MOQ
- Phase-matching available for group

### Applications

- Modules connection in receivers and transmitters
- Military and commercial systems


Outline Drawing Unit[mm]



### Electrical Specifications at 25°C

Freq. (GHz)	Length (m)	Insertion Loss (dB@GHz)								VSWR (@GHz)							
		DC.-6		6-12		12-18		18-26.5		DC.-6		6-12		12-18		18-26.5	
		Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.
DC- 26.5	0.1	0.5	0.6	0.6	0.8	0.7	1.0	0.8	1.2	1.15	1.20	1.26	1.30	1.31	1.35	1.38	1.45
	0.2	0.7	0.9	1.0	1.2	1.2	1.5	1.5	1.9								
	0.3	0.9	1.2	1.5	1.7	1.7	2.1	2.2	2.6								

### Cable Construction



Cable Construction	
Inner Conductor	Solid SPC
Dielectric	PTFE
Outer Conductor	Tin or Ternary Alloy Plated Copper

Connectors	
● Body, Berillium Copper, Gold plated	
● Center contacts, Berillium Copper, Gold plated	
● Dielectric, PTFE, Natural	

### Product Guarantee\*

Micable will repair or replace your cable assembly if it fails within six months after shipment. This guarantee excludes product damage from misuse or abuse

### Typical Performance Data (E01-37-38-0.2M)

Frequency(MHz)	VSWR	Insertion Loss (dB)
50	1.02	0.08
1000	1.04	0.31
2000	1.06	0.43
3000	1.09	0.55
4000	1.07	0.61
5000	1.10	0.65
6000	1.15	0.70
7000	1.11	0.75
8000	1.12	0.80
9000	1.17	0.85
10000	1.12	0.93
12000	1.26	1.00
13000	1.22	1.05
15000	1.16	1.09
18000	1.31	1.20
26500	1.38	1.50

