

# Power Divider/Combiner

## Model P12N265400 Rev.A

26.5-40GHz 12-Way Power Divider/Combiner, Coaxial connector



### Specifications

All specifications are subject to change without notice at any time

Frequency Range	GHz	26.5-40	
Sum VSWR	:1 (Max.)	1.7	
Distri. VSWR	:1 (Max.)	1.7	
Insertion Loss	<sup>1</sup> dB(Max.)	6	
Amp. Unbalance	dB(Max.)	±1	
Phase Unbalance	Deg. (Max.)	±14	
Isolation	dB(Min.)	16	
Power	<sup>2</sup> W(Max.)	CW: FOR 20, REV 2; Peak: 3000	
Weight	g(Max.)	420	Dimension <sup>3</sup> mm (LxWxH) 56.0x180.5x12.7
Interface	Stainless steel connector; Sum: 2.92mm [F], Distri.: 2.92mm [F]		
Finishing	Alloy iridite		
Temperature	Operating: -55~+85°C; Storage: -55~+100°C		
Environmental	Per MIL-STD-202F, Method 107D, 204D, 213B (optional, contact supplier for detail info.)		
Eng. Customized	N/A		

- Note:
- Above Theoretical Loss 10.8dB
  - VSWR ≤ 1.2 required for forward CW; Amp. & phase unbalance required for reversed input signals
  - Unless otherwise specified, Decimal tolerance: x.±1; .x±0.5; .xx±0.1

### Outline Drawing

