

F05J Series (N Male-ST to N Male-ST)

Jacketed .250 Hand Formable Cable Assembly, 50ohms, DC-18GHz



F05J-07-07-"L" (L: Length)

Maximum Ratings

Operating Temperature -55°C to +125°C

Storage Temperature -55°C to +125°C

Permanent damage may occur if any of these limits are exceeded

Outer Diameter	6.9 mm	
Velocity of Propagation	70%	
Shielding Effectiveness	>100dB	
Power Handling at 40°C	1 GHz	1000W
	2 GHz	739W
	6 GHz	407W
	12GHz	249W
	16 GHz	206W
18 GHz	190W	
Min. Bending Radius	30mm	

Features

- Excellent Return Loss/VSWR
- Hand formable to almost any custom shape without special bending tools
- Excellent shielding effectiveness >100 dB
- Anti-torque nut prevents cable stress during installation

Applications

- Replacement for .250" semi-rigid cables
- Modules connection in receivers and transmitters
- Interconnect of assembled systems
- Military and commercial systems


Electrical Specifications at 25°C

Freq. (GHz)	Length (m)	Insertion Loss (dB@GHz)								VSWR (@GHz)							
		DC - 3		3-6		6-12		12-18		DC - 3		3-6		6-12		12-18	
		Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.	Max.
DC-18	0.2	0.2	0.3	0.2	0.4	0.3	0.5	0.5	0.7	1.11	1.15	1.14	1.20	1.20	1.25	1.31	1.35
	0.3	0.3	0.4	0.4	0.5	0.5	0.6	0.7	0.9								
	0.5	0.4	0.6	0.6	0.8	0.7	0.9	0.9	1.2								
	1	0.6	0.8	0.9	1.2	1.3	1.6	1.6	1.9								


Typical Performance Data (F05J-07-07-1M)

Frequency(MHz)	VSWR	Insertion Loss (dB)
50	1.05	0.05
1000	1.08	0.34
2000	1.10	0.49
4000	1.12	0.77
5000	1.13	0.85
6000	1.14	0.91
7000	1.15	0.98
8000	1.16	1.06
9000	1.17	1.12
10000	1.18	1.23
12000	1.20	1.33
15000	1.25	1.45
16000	1.27	1.50
18000	1.30	1.61

Outline Drawing



Cable Construction



Cable Construction	
Inner Conductor	Solid SPC
Dielectric	PTFE
Outer Conductor	Tinned Soaked Copper Braid
Jacket	FEP

Connectors	
• Nut, Stainless steel, Passivated	
• Body, Brass, Gold plated	
• Center contacts, Brass, Gold plated	
• Dielectric, PTFE, Natural	

Product Guarantee*

Micable will repair or replace your cable assembly if it fails within six months after shipment. This guarantee excludes product damage from misuse or abuse

