

Amplifier

Model **MPA-265400S40** **Rev.A**

26.5-40GHz Solid State Power Amplifier

-Frequency range: 26.5-40GHz -Psat: $\geq 40\text{dBm}$, Gain: $\geq 40\text{dB}$

-Built-in control, monitoring and protection circuits

◆ Product Description

The MPA-265400S40 is a 26.5-40GHz, saturated power $\geq 40\text{dBm}$ high gain solid state power amplifier with state-of-art GaN design technology. It has higher saturated output power while keeping higher P1dB and better linearity, and can adapt to a variety of different signal modes such as continuous wave, pulse, wide instantaneous bandwidth signal, high-order modulation signal and etc. It is designed for applications, such as 5G & Millimeter Test System.

◆ Function

- Amplifying signal within 26.5-40GHz
- Over-VSWR, over-heating, over-current, over-voltage protection functions

Amplifier

◆ Electrical Specifications

Frequency Range	GHz		26.5-40
Saturated Output Power	dBm	Typ./Min.	41/40@ Pin=0dBm
P1dB	dBm	Typ./Min.	37/35
Gain	dB	Typ./Min.	41/40@ Pin=0dBm
Gain Flatness	dB	Typ.	±2.5@ Pin=0dBm
Small Signal Gain	dB	Typ.	45@ Pin=-30dBm
Small Signal Gain Flatness	dB	Typ.	±3@ Pin=-30dBm
Isolation@ Disable Status	dB	Typ.	90
Input Power	dBm	Typ.	0
Spurious Suppression	dBc	Typ./Max.	-70/-65@ Pout=40dBm
Input VSWR	:1	Typ./Max.	2/2.5
Switching Time	us	Typ.	2@ 1kHz TTL, Pin=0dBm
Supply Voltage	V	Typ.	28
Power Consumption	W	Typ.	150@ Pin=0dBm

◆ Limits

Input Power	Pin≤10dBm (Input RF level without damage)
Load VSWR	VSWR≤3:1 (Pout=40dBm)
	Power off (VSWR≥5:1 and Pout≥30dBm)
Supply Voltage	Power off (Supply Voltage≥32V or Supply Voltage≤24V)
Supply Current	Power off (Supply Current≥12A)
Thermal Degradation	75°C



Amplifier

Mechanical Specifications

RF Input Connector	2.92mm [F]
RF Output Connector	2.92mm [F]
Power supply Connector	D-Sub 7W2 [M]
Control Connector	D-Sub 7W2 [M]
Dimension	mm 100x100x25(LxWxH) (tolerance: ±0.5)
Weight	g Max. 700
Finishing	Alloy iridite
Temperature	Operating: -10°C~+55°C; Storage: -40°C ~ +75°C
Heat Dissipation ¹	External heat dissipation
Environmental ²	N/A

- Note: 1. Select heat dissipation conditions based on product temperature.
 2. Ititude, vibration and shock are designed with considerations, but without tests and experiments.


Outline Drawing



Amplifier

◆ Interface Connector Pin Out

D-Sub 7W2



A1.	GND	Ground
A2.	VDD	28 VDC
1.	Current Sensor	Analog voltage relative to IDD @ 100 mV per Ampere
2.	Temperature Sensor	Analog voltage relative to Module's Temperature @ 10 mV/°C
3.	Enable	Amplifier Disable: TTL Logic High (3.3 V), Internally pull down
4.	GND	Ground
5.	N/C	No Connection