

# Amplifier

---

**Model**    **MPAR-265400S42**    **Rev.A**

26.5-40GHz Solid State Power Amplifier

-Frequency range: 26.5-40GHz                      -Psat:  $\geq 42\text{dBm}$ , Gain:  $\geq 42\text{dB}$

-Built-in control, monitoring and protection circuits

---

## ◆ Product Description

The MPAR-265400S42 is a 26.5-40GHz, saturated power  $\geq 42\text{dBm}$  high gain solid state power amplifier with state-of-art GaN design technology. It has higher saturated output power while keeping higher P1dB and better linearity, and can adapt to a variety of different signal modes such as continuous wave, pulse, wide instantaneous bandwidth signal, high-order modulation signal and etc. It is designed for applications, such as 5G & Millimeter Test System.

## ◆ Function

- Amplifying signal within 26.5-40GHz
- Over-heating, over-excitation, over-VSWR protection and fan alarm functions

# Amplifier

## ◆ Electrical Specifications

Frequency Range	GHz		26.5-40
Saturated Output Power	dBm	Typ./Min.	43/42@ Pin=0dBm
P1dB	dBm	Typ./Min.	40/37
Gain	dB	Typ./Min.	43/42@ Pin=0dBm
Gain Flatness	dB	Typ.	±3.5@ Pin=0dBm
Small Signal Gain	dB	Typ.	48@ Pin=-30dBm
Small Signal Gain Flatness	dB	Typ.	±4.5@ Pin=-30dBm
Isolation@ Disable Status	dB	Typ.	90
Input Power	dBm	Typ.	0
Spurious Suppression	dBc	Typ./Max.	-70/-65@ Pout=42dBm
Input VSWR	:1	Typ./Max.	2/2.5
Supply Voltage	V	Typ.	110-240 (47-61Hz / Single-Phase)
Power Consumption	W	Typ.	450@ Pin=0dBm

## ◆ Limits

Input Power	Pin≤10dBm (Input RF level without damage)
Load VSWR	VSWR≤3:1 (Pout=42dBm)
	Power off (VSWR≥5:1 and Pout≥32dBm)
Thermal Degradation	75°C


# Amplifier

## ◆ Mechanical Specifications

RF Input Connector			2.92mm [F]
RF Output Connector			WR-28, Waveguide
Power supply Connector			3 WIRE A/C Power Entry (IEC320-C14 ,Including fuses)
Control Connector			D-Sub 9Pin
Dimension	mm		4U, 19 inch
Weight	kg	Max.	25
Finishing			Spraying plastics
Temperature			Operating: -10°C~+55°C; Storage: -40°C ~ +75°C
Heat Dissipation			Unit is cooled by air-forced condition
Environmental	1		N/A


Note: 1. Altitude, vibration and shock are designed with considerations, but without tests and experiments.

## ◆ Outline Drawing



# Amplifier

## ◆ Interface Connector Pin Out



### D-Sub 9Pin

	GND	Ground
1.	Shutdown	Amplifier Disable: TTL Logic High (3.3V) (Internally Pulled-Low)
2.	Temperature Alarm	Abnormal: Logic High (3.3V) (Internally Pulled-Low)
3.	Fan Alarm	Abnormal: Logic High (3.3V) (Internally Pulled-Low)
4.	Power Amplifier Alarm	Abnormal: Logic High (3.3V) (Internally Pulled-Low)
5.	N/C	No electrical connected, Reserved
6-9.		

## ◆ Front Panel LED Indicators

1.	RUN	GREEN: Internal power turn on, Amplifier is awoken and ready to work
2.	TEMP	RED: Temperature is over-limited, Amplifier shutdown
3.	FAN	RED: Fan is abnormal, Amplifier shutdown
4.	ALARM	RED: Amplifier is abnormal, Amplifier shutdown, Connect D-Sub 9 to debug