

4-Port 90° SMT Hybrid Coupler

Model Q5M050200 Rev.B

0.5-2GHz 4-Port 3dB 90° Hybrid, SMT



Specifications

All specifications are subject to change without notice at any time

Frequency Range	GHz	0.5-2
Nom. Phase	Deg. (Typ.)	90
Ports VSWR	:1 (Max.)	1.35
Insertion Loss ¹	dB(Max.)	0.5
Amp. Unbalance	dB(Max.)	±0.75
Phase Unbalance	Deg. (Max.)	±5
Isolation	dB(Min.)	16

PORT CONFIGURATION


INPUT	J1	J2	J3	J4
J1	-	ISO	0°	-90°
J2	ISO	-	-90°	0°
J3	0°	-90°	-	ISO
J4	-90°	0°	ISO	-



Power ²	W(Max.)	CW: 250		
Weight	g(Max.)	8	Dimension ³ mm (LxWxH)	12.70x45.72x4.80
Interface	Surface Mount			
Finishing	Immersion Gold			
Temperature	Operating: -55~+85°C; Storage: -55~+100°C			
Environmental	N/A			
Eng. Customized	N/A			

- Note:
- Above theoretical 3dB and amplitude unbalance
 - VSWR ≤ 1.2 required for CW
 - Unless otherwise specified, Decimal tolerance: x.±1; .x±0.5; .xx±0.25

Outline Drawing



4-Port 90° SMT Hybrid Coupler

Model Q5M050200 Rev.B

0.5-2GHz 4-Port 3dB 90° Hybrid, SMT

Typical Graph

Typical test temperature @25°C

